



WATERPROOF CANOPY

noribachi

FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> DIE-CAST ALUMINUM 	<ul style="list-style-type: none"> HIGH IMPACT POLYCARBONATE

ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- Available AC input: Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- Minimum CRI: 70
- Luminaire Efficacy(lm/W): 140.00
- CCT: 5700 K
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
21	35W	4,862lm

USES

- Best light output when placed 10-20 feet apart
- Average Height: 8 - 20 feet high
- Great for Parking Garages, Manufacturing, Logistics, Warehouses

MOUNTING

- Surface Mount

WARRANTY

- 5-year manufacturer's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Length: 12.38"
- Width: 12.38"
- Height: 8.63"

