



HAZARDOUS HIGH BAY

FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> Industrial strength die-cast aluminum 	<ul style="list-style-type: none"> Glass

ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- Available AC input: Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- Minimum CRI: 70
- Luminaire Efficacy(lm/W): 140.00
- CCT: 5700 K
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
84	138 W	19,448 lm

USES

- Best light output when placed 15-25 feet apart
- Average Height: 15 – 30 feet high
- Class 1, Division 2, Groups C, D, E, F, G
- Great for Manufacturing plants, Mine roadways, Warehouses, Heavy industrial chemical, petrochemical or pharmaceutical facilities and truck service stops

MOUNTING

- Handle Yoke

WARRANTY

- 5-year manufacturer's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Length: 12.00"
- Width: 12.00"
- Height: 3.36"

