



# RECTANGULAR HIGH BAY

**noribachi**

## FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> <li>Aluminum 3003</li> </ul>	<ul style="list-style-type: none"> <li>Optional: frosted polycarbonate</li> </ul>

## ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- Available AC input: Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

## LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- Minimum CRI: 70
- Luminaire Efficacy(lm/W): 140.00
- CCT: 5700 K
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
168	271W	37,970

## USES

- Great for Manufacturing, Parking Garages, Food Processing, Logistics, Warehouses, Service Bays, and Gyms

## MOUNTING

- Surface

## WARRANTY

- 5-year manufacturer's warranty
- U.S> manufacturing and quality control

## INSTALLATION

- Contact Noribachi for additional information

## CERTIFICATIONS



## FIXTURE DIMENSIONS

- Depth: 3.5"
- Length: 12"
- Width: 24"

