



ECONOMIC HO HIGH BAY

noribochi

FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> Die-cast Aluminum. IP65 	<ul style="list-style-type: none"> Prismatic Polycarbonate.

ELECTRICAL CHARACTERISTICS

- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFIT

- Minimum CRI: 70
- Color Temperature: 5700K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
63	104.10W	14,586lm

USES

- Convenience Stores, Gas Stations, Underpasses, Parking Garages, Walkways and a variety of other indoor and outdoor lighting applications.

MOUNTING

- Surface mount - Eye Hook for Pendant mount

WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Dimensions: 12.38" x 12.38" x 11.5"
- Weight: 3 lbs.
- Shipping Weight: 5 lbs.
- Standard Beam Angle: 120 Degrees

