



# PRISMATIC SURFACE MOUNT HIGH BAY

## FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> <li>Die-cast Aluminum.</li> <li>IP65</li> </ul>	<ul style="list-style-type: none"> <li>Prismatic Polycarbonate.</li> </ul>

## ELECTRICAL CHARACTERISTICS

- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

## LIGHT ENGINE RETROFIT

- Minimum CRI: 70
- Color Temperature: 5700K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
42	69.40W	9,724lm

## USES

- Convenience Stores, Gas Stations, Underpasses, Parking Garages, Walkways, medium indoor and a variety of other indoor and outdoor lighting applications.

## MOUNTING

- Surface Mount - Eye Hook for Pendant Mount

## WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

## INSTALLATION

- Contact Noribachi for additional information

## CERTIFICATIONS



## FIXTURE DIMENSIONS

- Dimensions: 16.0" x 11.0" x 12.25"
- Weight: 8.8 lbs.
- Shipping Weight: 11.7 lbs.
- Standard Beam Angle: 120 Degrees

