



# 100W LED AREALIGHT

## FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> <li>Die-cast Aluminum</li> <li>IP65</li> </ul>	<ul style="list-style-type: none"> <li>Clear standard.</li> </ul>

## ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

## LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 5000K
- L70 Rated life of 50,000+ hours
- Luminaire Efficacy(lm/W): 130.00 Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings

## AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
96	100W	13,000lm

## USES

- Parking lots, Urban roads, Industrial areas, Residential areas, Sidewalks, Schools, Gardens and various other outdoor applications.

## MOUNTING

- No mounting standard. Square pole, round pole and slip fitter optional

## WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

## INSTALLATION

- Contact Noribachi for additional information

## CERTIFICATIONS



## FIXTURE DIMENSIONS

- Length: 12.72"
- Width: 14.02"
- Height: 3.15"

