



# SECRET HIGH-OUTPUT LED FLOODLIGHT

## FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> <li>Industrial strength aluminum</li> <li>IP65</li> </ul>	<ul style="list-style-type: none"> <li>Polycarbonate</li> </ul>

## ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

## LIGHT ENGINE RETROFIT

- Minimum CRI: 70
- Color Temperature: 5700K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
96	158.40W	22,224lm

## USES

- Great option for stadiums, outdoor sport fields, parking lots, outdoor security, warehouses, billboards, landscapes, parks, other outdoor applications

## MOUNTING

- Handle yoke

## WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

## INSTALLATION

- Contact Noribachi for additional information

## CERTIFICATIONS



## FIXTURE DIMENSIONS

- Height: 20.0"
- Diameter: 21.0"
- Length with mount: 31.0"

