



ZIPPY-HEX-140

noribachi

FIXTURE APPEARANCE

HOUSING	LENS
• Not Applicable	• Not Applicable

ELECTRICAL CHARACTERISTICS

- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 5700K, Optional: 300K, 4000K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
140	220.50W	30,870lm

USES

- Great option for manufacturing facilities, storage areas, warehouses, service bays, gymnasiums, atriums, aquatic centers, sport complexes

MOUNTING

- Magic tab mounting

WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Length: 15.5"
- Width: 12.75"
- Depth: 2.72"
- Minimum size of luminaire interior: 15.75"L x 15.75"W x 5"D

