



4' LINEAR HIGH BAY SHOP LIGHT

FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> Polycarbonate IP65 	<ul style="list-style-type: none"> Frosted polycarbonate

ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 3000k, 4000k, or 5700K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
84	90.20W	14,432lm

USES

- Great for Manufacturing, Parking Garages, Food Processing, Logistics, Warehouses, Service Bays, and Gyms

MOUNTING

- Surface mount, bracket optional

WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Length: 50"
- Width: 6.75"
- Height: 5.63"

