



RIBBED DOME PENDANT

FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> Spun Aluminum 	<ul style="list-style-type: none"> Optional clear or frosted

ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
42	46.40W	6,482lm

USES

- Restaurants, Households, Hotels, Workshops and other indoor location where task lighting is needed.

MOUNTING

- Pendant

WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Height: 10"
- Diameter: 9.36"
- Ceiling mount diameter: 8"
- Hanging length (max): 48"

FIXTURE FEATURES

- Mounting system included
- 4 ft (max) suspension system included
- Ceiling mount finish: Polished nickel

