



# HANGING SHOP LIGHT

## FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> <li>Aluminum</li> </ul>	<ul style="list-style-type: none"> <li>Optional frosted or clear lens</li> </ul>

## ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

## LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 5700K, Optional 3000K, 4000K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
112	39.20W	4,308lm
224	78.40W	8,616lm

## USES

- Great option for hallways, task lighting, work shops, work benches, utility areas, garages, basements, kitchens

## MOUNTING

- Hanging system with aircraft cable. Includes ability to adjust cable length.

## WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

## INSTALLATION

- Contact Noribochi for additional information

## CERTIFICATIONS



## FIXTURE DIMENSIONS

- Length: 48"
- Width: 6"
- Depth: 3"

## FIXTURE FEATURES

- 6 ft of of power cord and plug included
- Corrosion and scratch resistant
- Smooth edges for easy handling
- Knockouts on ends allow continuous wire way mounting
- Strain release on power cord coming out of fixture
- Hardware included:, 6 feet of cable for fixture suspension

