



HANGING SHOP LIGHT

FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> Aluminum 	<ul style="list-style-type: none"> Frosted

ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 5700K, Optional 3000K, 4000K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
224	78.40W	8,616lm

USES

- Great option for hallways, task lighting, work shops, work benches, utility areas, garages, basements, kitchens

MOUNTING

- Hanging system with aircraft cable. Includes ability to adjust cable length.

WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Length: 48"
- Width: 6"
- Depth: 3"

FIXTURE FEATURES

- P3 technology - Post Powder Paint > 90% reflectivity
- Corrosion and scratch resistant
- Smooth edges for easy handling
- 90 degree sides for easy side wiring
- Knockouts on ends allow continuous wire way mounting
- 1/2" regressed flange at the bottom insures uniformity and rigidity
- Hardware included: 6 ft of wiring and easy to use compact splicing connectors, 6 feet of cable for fixture suspension

