



# PORTABLE LED WORK LIGHT

noribachi

## FIXTURE APPEARANCE

HOUSING	LENS
<ul style="list-style-type: none"> <li>Die-cast aluminum housing and durable powder coat finish</li> </ul>	<ul style="list-style-type: none"> <li>Tempered glass lens with metal safety grill</li> </ul>

## ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

## LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 5700K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
42	69.40W	9,724lm

## USES

- Great option for manufacturing facilities, storage areas, warehouses, service bays, gymnasiums, atriums, aquatic centers, sport complexes

## MOUNTING

- Not Applicable

## WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

## INSTALLATION

- Contact Noribachi for additional information

## CERTIFICATIONS



## FIXTURE DIMENSIONS

- Dimensions: Height: 69.88" x Width: 9.05" x Length: 22.44"

## FIXTURE FEATURES

- Tripod stand, non-skid feet, height adjustment with flip lock
- Height adjusts to over 4.85 feet
- Quick-release clamp permits easy removal of light head from stand

