



HIGH BAY RETROFIT KIT

FIXTURE APPEARANCE

HOUSING	LENS
• Not Applicable	• Not Applicable

ELECTRICAL CHARACTERISTICS

- AC Input (Standard): 120/277 VAC
- AC Input (available): Up to 480 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard
- High Voltage

LIGHT ENGINE RETROFIT

- Minimum CRI: 80
- Color Temperature: 3000K, 4000K, 5700K
- L70 Rated life of 100,000+ hours
- Luminaire Efficacy(lm/W): 140.00
- Operating temp: -30 C to +60 C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE LIGHT ENGINES

LED COUNT	WATTAGE	DELIVERED LUMENS
24	39.60W	5,556lm

USES

- Convert your existing lighting fixtures to bright and efficient LED lighting

MOUNTING

- Universal mounting kit with 6" all-thread

WARRANTY

- 5-year manufacture's warranty
- U.S> manufacturing and quality control

INSTALLATION

- Contact Noribachi for additional information

CERTIFICATIONS



FIXTURE DIMENSIONS

- Length: 1.79"
- Width: 1.79"
- Height: 6"

